

IN THE CLAIMS:

A marked-up version of the amended claims, including insertions and deletions, is attached as Appendix B. A complete set of currently pending claims, reflecting these amendments, is attached as Appendix C.

Please rewrite claims 1, 4, 6, 7, 10, 13, 15, 16, 19, and 23 to read as follows:

into CY
a 2
1. (Amended) A drum comprising:

a side wall comprising a plurality of side wall sections connected by corner sections, the side wall having end portions disposed at longitudinal ends thereof;

first and second end walls located adjacent the end portions, the first end wall defining a fill/drain opening therein;

a circumferential carrying and transport rim disposed on at least one of the end portions and configured for carrying the drum with drum handling equipment; and

a first indentation formed on the side wall substantially intermediate the end portions, the first indentation configured and dimensioned to resist buckling of the side wall, wherein the drum defines a longitudinal axis between the end portions, and the indentation extends substantially circumferentially about the side wall around the longitudinal axis and is substantially V-shaped only at the corner sections.

a 3
4. (Amended) The drum of claim 1, wherein the side wall sections define a substantially rectangular cross-section of the side wall, and the first indentation defines a substantially circular cross-section of the side wall.

a 4
6. (Amended) The drum of claim 1, wherein the drum defines a drum height between the end portions and substantially parallel to the longitudinal axis, and the first indentation is disposed in a plane located at about 30% to about 70% of the drum height.

7. (Amended) The drum of claim 1, wherein the side wall further comprises a second indentation formed thereon, and the second indentation extends substantially in a direction of the longitudinal axis.

a 5
10. (Amended) A drum comprising:
a side wall comprising:

a first portion having a plurality of side wall sections that define a first circumferential cross-section,

a second portion comprising angular indentations in the side wall disposed at intersections between the side wall sections defining a second circumferential cross-section that is different than the first cross-section and configured and dimensioned to resist buckling of the side wall, and

end portions disposed at longitudinal ends of the side wall;

first and second end walls located adjacent the end portions, the first end wall comprising a recessed well; and

a fill/drain opening defined in the recessed well;

wherein the first cross-section is substantially rectangular, and the second cross-section is substantially circular.

13. (Amended) The drum of claim 10, wherein the first cross-section is substantially square.

15. (Amended) The drum of claim 10, wherein the angular indentations are substantially V-shaped and are deepest at the intersections and transition into the side wall sections such that the second cross-section is substantially circular.

16. (Amended) The drum of claim 15, wherein the indentations are spaced apart a predetermined distance such that each indentation does not transition into each adjacent indentation.

19. (Amended) A drum comprising:

a side wall comprising a first portion having a plurality of side wall sections that define a substantially rectangular first cross-section of the side walls, the side wall having end portions disposed at longitudinal ends thereof;

a protrusion formed in the side wall substantially intermediate the end portions to resist buckling of the side wall, the protrusion defining a substantially circular second cross-section of the side wall;

first and second end walls located adjacent the end portions, the first end wall defining a fill/drain opening; and

a circumferential carrying and transport rim disposed on at least one of the end portions and configured for carrying with drum handling equipment.

9
a 23. (Amended) The drum of claim 19, wherein the protrusion extends substantially circumferentially.

Please cancel claims 2, 3, 5, 14, 21, and 24, without prejudice.

Please add the following new claims:

29. (New) The drum of claim 1, wherein the first indentation is deepest at the corner sections and becomes shallower as it transitions into the side wall sections.

30. (New) The drum of claim 1, wherein the first indentation is substantially V-shaped in a plane extending substantially parallel to the longitudinal axis.

10
a 31. (New) The drum of claim 19, wherein the drum defines a drum height between the end portions, and the protrusion is disposed in a plane located at about 30% to about 70% of the drum height.

32. (New) The drum of claim 19, wherein the first cross-section is substantially square.

33. (New) The drum of claim 19, wherein the side wall sections are joined by corner sections, and the protrusion is substantially V-shaped at the corner sections.

34. (New) A drum comprising:
a side wall comprising a plurality of side wall sections connected by corner sections, the side wall having end portions disposed at longitudinal ends thereof;
first and second end walls located adjacent the end portions, the first end wall defining a fill/drain opening therein;
a circumferential carrying and transport rim disposed on the drum and configured for carrying the drum with drum handling equipment; and
an angular indentation formed on the side wall substantially intermediate the end walls, wherein the indentation is deeper at the corner sections than it is at a point on at least one of the side wall sections intermediate the corner sections.

35. (New) The drum of claim 34, wherein the indentation is substantially flat at a point on the side wall sections intermediate the corner sections.

CFNS.
112nd. New
Halt

36. (New) The drum of claim 34, wherein the indentation is substantially V-shaped only at the corner sections.

37. (New) The drum of claim 34, wherein the drum defines a longitudinal axis between the end walls, and the indentation is substantially V-shaped in a plane extending substantially parallel to the longitudinal axis.

38. (New) The drum of claim 34, wherein the side wall sections define a first circumferential cross-section that is substantially square, and the angular indentation defines a second circumferential cross-section that is substantially circular.

a¹⁰
39. (New) A drum comprising:
a side wall comprising a plurality of side wall sections connected by corner sections, the side wall having end portions disposed at longitudinal ends thereof;
first and second end walls located adjacent the end portions, the first end wall defining a fill/drain opening therein;
a circumferential carrying and transport rim disposed on the drum and configured for carrying the drum with drum handling equipment; and
an indentation formed on the side wall substantially intermediate the end walls, wherein the indentation defines a vertical thickness that varies around the circumference of the side wall.

40. (New) The drum of claim 39, wherein the thickness is greatest at the corner sections.

41. (New) The drum of claim 39, wherein the thickness is smallest at a point on at least one of the side wall sections substantially intermediate the corner sections.

42. (New) The drum of claim 39, wherein the thickness is substantially zero at a point on at least one of the side wall sections substantially intermediate the corner sections.

Very
Much

43. (New) The drum of claim 39, wherein the indentation is substantially V-shaped only at the corner sections.

44. (New) The drum of claim 39, wherein the side wall sections define a first circumferential cross-section that is substantially square, and the indentation defines a second circumferential cross-section that is substantially circular.

45. (New) A drum comprising:
a side wall comprising a plurality of side wall sections connected by corner sections, the side wall having end portions disposed at longitudinal ends thereof;
first and second end walls located adjacent the end portions, the first end wall defining a fill/drain opening therein;
a circumferential carrying and transport rim disposed on the drum and configured for carrying the drum with drum handling equipment; and
an indentation formed on the side wall substantially intermediate the end walls;
wherein:
the indentation defines a vertical thickness that varies around the circumference of the side wall; and
the indentation is deeper at the corner sections than it is at a point on at least one of the side wall sections intermediate the corner sections.